



MATERIAL SAFETY DATA SHEET

UNBRANDED CONVENTIONAL GASOLINE [ALL GRADES]

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: UNBRANDED CONVENTIONAL GASOLINE [ALL GRADES]
SUPPLIER: GULF OIL LIMITED PARTNERSHIP
275 WASHINGTON STREET, SUITE 300
NEWTON, MASSACHUSETTS 02458-1646

Emergency:
CHEMTREC: 800-424-9300

MSDS Internet Website: WWW.GULFOIL.COM

1. EMERGENCY OVERVIEW

HEALTH HAZARDS/PRECAUTIONARY MEASURES: May be harmful or fatal if swallowed. Aspiration hazard. Possible cancer hazard based on animal data. Vapor harmful. Causes skin irritation. Use ventilation adequate to keep exposure below recommended limits, if any. Avoid breath vapor or mist. Avoid contact with eyes, skin and clothing. Do not taste or swallow. Wash thoroughly after handling

PHYSICAL HAZARDS/PRECAUTIONARY MEASURES: Extremely flammable liquid and vapor. Vapor can cause flash fire. Keep away from heat, sparks, flames, static electricity or other sources of ignition.

APPEARANCE: Clear to amber
PHYSICAL FORM: Liquid
ODOR: Gasoline

NEPA HAZARD CLASS: Health: 1 (Slight), Flammability: 3 (High),
Reactivity: 0 (Least)

NMIS HAZARD CLASS: Health 2* (Moderate), Flammability: 3 (High),
Physical Hazard: 0 (Least)

*Indicates possible chronic health effects

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>HAZARDOUS COMPONENTS</u>	<u>% WEIGHT</u>	<u>EXPOSURE GUIDELINE</u>		
		<u>Limits</u>	<u>Agency</u>	<u>Type</u>
Gasoline CAS# None	88-100	300 ppm 500 ppm	ACGIH ACGIH	TWA STEL
Xylenes CAS # 1330-20-7	1-14	100 ppm 150 ppm 100 ppm 900 ppm	ACGIH ACGIH OSHA NIOSH	TWA STEL TWA IDLH
Toluene CAS# 108-88-3	1-9	50 ppm 200 ppm 300 ppm 500 ppm 500 ppm	ACGIH OSHA OSHA NIOSH OSHA	TWA-SKIN TWA <u>CEIL</u> IDLH 10 min. peak; Once per 8-hr shift
1,2,-4 Trimethyl Benzene CAS# 95-63-6	1-5	25 ppm (Mixed Isomers)	ACGIH	TWA
Benzene	0.4-5	0.5 ppm 2.5 ppm 1 ppm 5ppm 500 ppm	ACGIH ACGIH OSHA OSHA NIOSH	TWA_SKIN STEL-SKIN TWA STEL IDLH
Ethyl Benzene CAS# 100-41-4	1-5	100 ppm 125 ppm 100 PPM 800 ppm	ACGIH ACGIH OSHA NIOSH	TWA STEL TWA IDLH
n-Hexane	0-4	50 ppm 500 ppm 1100 ppm	ACGIH OSHA NIOSH	TWA-SKIN TWA IDLH
Cyclohexane	0-2	100 ppm 300 PPM 1300 ppm	ACGIH OSHA NIOSH	TWA TWA IDLH

Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.

1%=10,000 PPM

Contains benzene. If exposure concentrations exceed the 0.5 ppm action level, OSHA requirements for personal protective equipment, exposure monitoring, and training may apply (29CFR1910.1028). Also see Section 4.

3. HAZARDS IDENTIFICATION

EYE: Contact may cause mild eye irritation including stinging, watering and redness.

SKIN: Skin irritant. Contact may cause redness, itching, burning and skin damage. Prolonged or repeated contact can worsen irritation by causing drying and cracking of the skin, leading to dermatitis (inflammation). Not acutely toxic by skin absorption, but prolonged or repeated skin contact may be harmful (see Section 11).

INHALATION (BREATHING): Low to moderate degree of toxicity by inhalation.

INGESTION (SWALLOWING): Low degree of toxicity by ingestion. ASPIRATION HAZARD - This material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

SIGNS AND SYMPTOMS: Effects of overexposure may include nausea, vomiting, flushing, transient excitation followed by signs of nervous system depression (e.g. headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue), blurred vision, tremors, respiratory failure, unconsciousness, convulsions and death.

CANCER: Possible cancer hazard (see Sections 11 and 15).

TARGET ORGANS: Inadequate evidence available for this material. See Section 11 for target-organ toxicity information of individual components, if any.

DEVELOPMENTAL: No harm to the fetus was observed in laboratory animal studies.

OTHER COMMENTS: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as Solvent or Painters' Syndrome). Intentional misuse by deliberately concentrating and inhaling this material may be harmful or fatal.

PRE-EXISTING MEDICAL CONDITIONS: Conditions aggravated by exposure may include skin disorders and respiratory (asthma-like) disorders.

Exposure to high concentrations of this material may increase the sensitivity of the heart to certain drugs. Persons with pre-existing heart disorders may be more susceptible to this effect (see Section 4 - Note to Physicians).

4. FIRST AID MEASURES

EYE: If irritation or redness develops, move victims away from exposure and into fresh air. Flush eyes with clean water. If symptoms persist, seek medical attention.

SKIN: Remove contaminated shoes and clothing, and flush affected area(s) with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected

area(s) thoroughly by washing with mild soap and water. If irritation or redness develops, seek medical attentions.

INHALATION (BREATHING): If respiratory symptoms or other symptoms of exposure develop, move victim away from source of exposure and into fresh air. If symptoms persist, seek immediate medical attention. If victim is not breathing, clear airway and immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

INGESTION (SWALLOWING): Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. If victim is drowsy or unconscious and vomiting, place on the left side with the head down. If possible, do not leave victim unattended and observe closely for adequacy of breathing. Seek medical attention.

NOT TO PHYSICIANS: Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias if personal exposed to high concentrations of hydrocarbon solvents (e.g., in enclosed spaces or with deliberate abuse). The use of other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs are administered, observe for the development of cardiac arrhythmias.

Federal regulations (29 CFR 1910.1028) specify medical surveillance programs for certain exposures to benzene above the action level or PEL (specified in Section (i)(1)(i) of the Standard). In addition, employees exposed in an emergency situation shall, as described in Section (i)(4)(i), provide a urine sample at the end of the shift for measurement of urine phenol.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES: Flash Point: -49°F/-45°C
 OSHA Flammability Class: Flammable Liquid
 LEL%: 1.4 / UEL%: 7.6
 Autoignition Temperature: 833°F/444°C

UNUSUAL FIRE & EXPLOSION HAZARDS: This material is extremely flammable and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). Vapors may travel considerable distances to a source of ignition where they can ignite, flash back, or explode. May create vapor/air explosion hazard indoors, in confined spaces, outdoors, or in sewers. Vapors are heavier than air and can accumulate in low areas. If container is not properly cooled, it can rupture in the heat of a fire.

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, or foam is recommended. Water spray is recommended by cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Water may be ineffective for extinguishment, unless used under favorable conditions by experienced fire fighters.

FIRE FIGHTING INSTRUCTIONS: For fires beyond the incipient stage emergency responders in the immediate hazard area should wear bunker gear. When the potential chemical hazard is unknown, in enclosed or confined spaces, or when

explicitly required by DOT, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8).

Isolate immediate hazard area, keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Move undamaged containers from immediate hazard area if it can be done with minimal risk.

Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

6. ACCIDENTAL RELEASE MEASURES

EXTREMELY FLAMMABLE. Keep all sources of ignition and hot metal surfaces away from spill/release. The use of explosion-proof equipment is recommended.

Stay upwind and away from spill/release. Notify persons down wind of the spill release, isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Water appropriate protective equipment including respiratory protection as conditions warrant (see Section 8.)

Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems, and natural waterways. Dike far ahead of spill for later recovery or disposal. Use foam on spills to minimize vapors (see Section 5). Spilled material may be absorbed into an appropriate absorbent material.

Notify fire authorities and appropriate federal, state and local agencies. Immediate cleanup of any spill is recommended. If spill of any amount is made into or upon navigable waters, the contiguous zone, or adjoining shorelines, notify the National Response Center (phone number 800-424-8802).

7. HANDLING AND STORAGE

HANDLING: Open container slowly to relieve any pressure. Bond and ground all equipment when transferring from one vessel to another. Can accumulate static charge by flow or agitation. Can be ignited by static discharge. The use of explosion-proof equipment is recommended any may be required (see appropriate fire codes).

Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146. The use of appropriate respiratory protection is advised when concentrations exceed any established exposure limits (see Sections 2 and 8).

Wash thoroughly after handling. Do not wear contaminated clothing or shoes. Keep contaminated clothing away from sources of ignition such as sparks or open flames. Use good personal hygiene practices.

High pressure injection of hydrocarbon fuels, hydraulic oils or greases under the skin may have serious consequences even though no symptoms or injury may

be apparent. This can happen accidentally when using high pressure equipment such as high pressure grease guns, fuel injection apparatus or from pinhole leaks in tubing or high pressure hydraulic oil equipment.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder drill, grind, or exposure such containers to heat flame, sparks or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

Before working on or in tanks which contain or have contained this material, refer to OSHA regulations, **ANSI Z49.1** and other referenced pertaining to cleaning, repairing, welding, or other contemplated operations.

STORAGE: Keep container(s) tightly closed. Use and store this material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Post area "No Smoking or Open Flame." Store only in approved containers. Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage. Outdoor or detached storage is preferred. Indoor storage should meet OSHA standards and appropriate fire codes.

PORTABLE CONTAINERS: Static electricity may ignite gasoline vapors when filling portable containers. To avoid static buildup do not use a nozzle lock open device. Use only approved containers for the storage of gasoline. Place the container on the ground before filling. Keep the nozzle in contact with the container during filling.

Do not fill any portable container in or on a vehicle or marine craft.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

ENGINEERING CONTROLS: If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits (see Section 2), additional engineering controls may be required. Where explosive mixtures may be present, electrical systems safe for such locations must be used (see appropriate electrical codes).

PERSONAL PROTECTIVE EQUIPMENT (PPE):

RESPIRATORY: A NIOSH certified air purifying respirator with an organic vapor cartridge may be used under conditions where airborne concentrations are expected to exceed exposure limits (see Section 2).

Protection provided by air purifying respirators is limited (see manufacturer's respirator selection guide). Use a NIOSH approved self-contained breathing apparatus (SCBA) or equivalent operated in a pressure demand or other positive pressure mode if there is potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

A respiratory protection program that meets **OSHA's 29 CFR 1910.134 and ANSI Z88.2** requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN: The use of gloves impervious to the specific material handled is advised to prevent skin contact, possible irritation, and skin damage. Examples of approved materials are nitrile, or Viton® (**see glove manufacturer literature for information on permeability**). Depending on conditions of use, apron and/or arm covers may be necessary.

EYE/FACE: Approved eye protection to safeguard against potential eye contact, irritation, or injury is recommended. Depending on conditions of use, a face shield may be necessary.

OTHER PROTECTION EQUIPMENT: A source of clean water should be available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.

Suggestions for the use of specific protective materials are based on readily available published data. Users should check with specific manufacturers to confirm the performance of their products.

9. PHYSICAL AND CHEMICAL PROPERTIES

Note: Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm).

Appearance: Clear to amber

Physical State: Liquid

Odor: Gasoline

pH: Not applicable

Vapor Pressure (mm Hg): 350-760 @ 100°F

Vapor Density (air=1): >1

Boiling Point/Range: 80-440°F / 26-227°C

Freezing/Melting Point: No Data

Solubility in Water: Negligible

Specific Gravity: 0.72 - 0.75 @ 60°F

Percent Volatile: 100 vol.%

Evaporation Rate (nBuAc=1):>1

Bulk Density: 6.17 lbs/gal

Flash Point: -49°F / -45°C

Flammable/Explosive Limits (%): LEL: 1.4 / UEL: 7.6

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure. Extremely flammable liquid and vapor. Vapor can cause flash fire.

CONDITONS TO AVOID: Avoid all possible sources of ignition (see Sections 5 and 7)

MATERIALS TO AVOID (INCOMPATIBLE MATERIALS); Contact with strong oxidizing agents such as chlorine, dichromates, or permanganates can cause fire or explosion.

HAZARDOUS DECOMPOSITION PRODUCTS: The use of hydrocarbon fuel in an area without adequate ventilation may result in hazardous levels of combustion products (e.g., oxides of carbon, sulfur and nitrogen, benzene and other hydrocarbons) and/or dangerously low oxygen levels. See Section 11 for additional information on hazards of engine exhaust, if any.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

GASOLINE (CAS# NONE)

CARCINOGENICITY: Two year inhalation studies of wholly vaporized unleaded gasoline produced increased incidences of kidney tumors in male rats and liver tumors in female mice. Follow-up studies suggest that occurrence of the kidney tumors may be linked to alpha-2-uglobulin nephropathy, and most likely unique to the male rat. Epidemiology data collected from study or more than 18,000 petroleum marketing and distribution workers showed no increased risk of leukemia, multiple myeloma, or kidney cancer from gasoline exposure. Unleaded gasoline has been identified **as a possible carcinogen by IARC.**

Because solvent extracts of gasoline exhaust particulates caused skin cancer in laboratory animals, IARC has categorized gasoline engine exhaust as a possible human cancer hazard.

TARGET ORGAN(S): A two year inhalation study of wholly vaporized unleaded gasoline produced nephropathy in male rats, characterized by the accumulation of alpha-2-u globulin in epithelial cells of the proximal tubules, and necrosis and hyperplasia of surrounding cells. Follow-up studies have demonstrated that these changes are unique to the male rat.

Although prolonged exposure to n-hexane, a component of gasoline, has resulted in adverse male reproductive effects in experimental animal studies, no adverse male reproductive effects were found in studies conducted with gasoline.

DEVELOPMENT: No evidence of developmental toxicity was found in pregnant laboratory animals (rats and mice) exposed to up to 9,000 ppm vapor of unleaded gasoline via inhalation.

XYLENES (CAS#1330-20-7)

TARGET ORGAN(S): A six week inhalation study with xylene produced hearing loss in rats.

DEVELOPMENTAL: Exposure to toluene during pregnancy has demonstrated limited evidence of developmental toxicity in laboratory animals. The effects seen include decreased fetal body weight and increased skeletal variations in both inhalation and oral studies.

BENZENE (CAS#71-43-2)

CARCINOGENICITY: Benzene is an animal carcinogen and is known to product acute

myelogenous leukemia (a form of cancer) in humans. Benzene has been identified as a human carcinogen by NTP, IARC and OSHA.

TARGET ORGAN(S): Prolonged or repeated exposures to benzene vapors has been lined to bone marrow toxicity which can result in blood disorders such as leucopenia, thrombocytopenia, and aplastic anemia. All of these diseases can be fatal.

DEVELOPMENTAL: Exposure to benzene during pregnancy demonstrated limited evidence of developmental toxicity in laboratory animals. The effects seen include decreased body weight and increased skeletal variations in rodents. Alternations in hematopoeisis have been observed in the fetuses and offspring of pregnant mice.

MUTAGENICITY: Benzene exposure has resulted in chromosomal aberrations in human lymphocytes and animal bone marrow cells, and DNA damage in mammalian cells in vitro.

ETHYL BENZENE (CAS@ 100-41-4)

CARCINOGENICITY: Rats and mice exposed to 0, 75, 250, 750 ppm ethyl benzene in a two year inhalation study demonstrated limited evidence of kidney, liver and lung cancer. Ethyl benzene has been listed as a possible human carcinogen by **IARC**. Ethyl benzene has not been listed as a carcinogen by NTP or OSHA.

TARGET ORGAN(S): In rats and mice exposed to 0, 75, 250, 750 ppm ethyl benzene in a two year inhalation study there was mild damage to the kidney (tubular hyperplasia), liver (eosinophilic foci, hypertrophy, necrosis), thyroid (hyperplasia) and pituitary (hyperplasia).

n-HEXANE (CAS#110-54-3)

TARGET ORGAN(S): Excessive exposure to n-hexane can result in peripheral neuropathies. The initial symmetrical sensory numbness and parasthesias of distal portions of the extremities. Motor weakness is typical observed in muscles of the toes and fingers but may also involve muscles of the arms, thighs and forearms. The onset of these symptoms may be delayed for several months to a year after the beginning of exposure. The neurotoxic properties of n-hexane are potentiated by exposure to methyl ethyl ketone and methyl isobutyl ketone.

Prolonged exposure to high concentrations of n-hexane (>1,000 ppm) has resulted in decreased sperm count and degenerative changes in the testes of rats but not those of mice.

Acute Data:

Gasoline:

Dermal LD50>5 ml/kg (Rabbit)

LC50>4500 ppm (Rat)

Oral LD50=18.75 ml/kg. (Rat)

1, 2, 4-Trimethyl Benzene:

Dermal LD50 = No data available

LC50 = 18 gm/m³/4hr (Rat)

Oral LD50-3-6 g/kg (Rat)

Benzene:

Dermal LD50>9400 mg/kg (Rabbit), (Guinea Pig)
LC50=9980 ppm (Mouse); 10000 ppm/7 hr. (Rat)
Oral LD50=4700 mg/kg (Mouse); 930 mg/kg (Rat); 5700 mg/kg (Mammal)

Cyclohexane:

Dermal LD50=>2/kg (Rabbit)
LC50>4,044 ppm (4-hr., Rat)
Oral LD50>2g/kg (Rat)

Ethyl Benzene:

Dermal LD50=17800 mg/kg (Rabbit)
LC50=4000 ppm/4 hr.; 13367 ppm (Rat)
Oral LD50=3500 mg/kg (Rat)

n-Hexane:

Dermal LD50=>2,000 mg/kg (Rabbit)
LC50>3,367 ppm (r-hr., Rat)
Oral LD50>5,000 mg/kg (Rat)

Toluene:

Dermal LD50=14 g/kg (Rabbit)
LC50=8,000 ppm (4-hr., Rat)
Oral LD50=2.5 - 7.9 g/kg (Rat)

Xylene:

Dermal LD50>3.16 ml/kg (Rabbit)
LC50=5000 ppm/4 hr. (Rat)
Oral LD50=4300 mg/kg (Rat)

12. ECOLOGICAL INFORMATION

Spilling of gasoline can result in environmental damage.

Gasoline floats on water and evaporates rapidly from water or soil surfaces. However, spilled gasoline may penetrate soil and could contaminate groundwater.

Gasoline is biodegradable but in situations of low oxygen, such as in soil below grade or in groundwater, may persist for many years.

Gasoline does not readily dissolve in water but will be adsorbed to soils. Gasoline in the environment can be toxic to plants and animals.

13. DISPOSAL CONSIDERATIONS

This materials, if discarded as produced, would be a RCRA "characteristic" hazardous waste due to the characteristic(s) **of ignitability (D001) and benzene (D018)**. If the spilled or released material impacts soil, water, or other media, characteristic testing of the contaminated materials may be required prior to their disposal. Further, this material, once it becomes a waste, **is subject to the land disposal restrictions in 40 CFR 268.40** and may require treatment prior to disposal to meet specific standards. Consult state and local regulations to determine whether they are more stringent than the federal requirements.

Container contents should be completely used and containers should be emptied prior to discard. Container rinsate could be considered a RCRA hazardous waste and must be disposed of with care and in full compliance with federal, state and local regulations. Larger empty containers, such as drums, should be returned to the distributor or to a drum reconditioner. To assure proper disposal of smaller empty containers, consult with state and local regulations and disposal authorities.

14. TRANSPORT INFORMATION

DOT Shipping Description: Gasoline, 3, UN1203, II
Non-Bulk Package Marking: Gasoline, UN1203
Non-Bulk Package Label: Flammable
Bulk Package Placard/Marking: Flammable/1203
Hazardous Substance/RQ: None
Packaging References: 49 CFR 173.150, 173.202, 173.242
Emergency Response Guide: 128

15. REGULATORY INFORMATION

Acute Health: Yes
Chronic Health: Yes
Fire Hazard: Yes
Pressure Hazard: No
Reactive Hazard: No

SARA 313 and 40 CFR372

This material contains the following chemicals subject to the reporting requirements of SARA 313 and 40 CFR 372.

Component	CAS Number	Weight%
Xylenes	1330-2-7	1-14
Toluene	108-88-3	1-9
1,2, 4-Trimethyl Benzene	95-63-6	1-5
Benzene	71-43-2	0.4-5
Ethyl Benzene	100-41-4	1-5
n-Hexane	110-54-3	0-4
Cyclohexane	110-82-7	0-2

CALIFORNIA PROPOSITION 65:

WARNING: This material contains the following chemicals which are known in the State of California to cause cancer, birth defects or other reproductive harm, and are subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

<u>Component</u>	<u>Effect</u>
Benzene	Cancer, Developmental and Reproductive Toxicant
Toluene	Developmental Toxicant
Unleaded Gasoline (wholly vaporized)	Cancer

CARCINOGEN IDENTIFICATION

Unleaded gasoline has been identified as a carcinogen by IARC. For carcinogenicity information on individual components, see Section 11.

EPA (CERCLA) REPORTABLE QUANTITY: None

Cananda - Domestic Substance List: Listed

WHMIS Class:

B2-Flammable Liquid

D2B-Materials causing other toxic effects - Toxic Materials

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

Issue Date: May 2007

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT. Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. Gulf Oil Limited Partnership assumes no responsibility for accuracy of information unless the document is the most current available from an official Gulf Oil Limited Partnership distribution system. Gulf Oil Limited Partnership neither represent nor warrant that the format, content or product formulas contained in this document comply with the laws of any other country except the United States of America.