



MATERIAL SAFETY DATA SHEET

SUPER UNLEADED GASOLINE

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SUPER UNLEADED GASOLINE
SUPPLIER: GULF OIL LIMITED PARTNERSHIP
275 WASHINGTON STREET, SUITE 300
NEWTON, MASSACHUSETTS 02458-1646

Emergency:
CHEMTREC: 800-424-9300

MSDS Internet Website: WWW.GULFOIL.COM

2. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAMES AND SYNONYMS: HYDROCARBON

INGREDIENTS CONSIDERED HAZARDOUS TO HEALTH:

Substance Name	Wt%
SUPER UNLEADED GASOLINE	100

COMPONENT(S) OF PRODUCT INGREDIENTS INCLUDE:

BENZENE (71-43-2)	2
-------------------	---

See Section 15 for European Label Information.

See Section 8 for exposure limits (if applicable).

3. HAZARDS IDENTIFICATION

US OSHA HAZARD COMMUNICATION STANDARD: Product assessed in accordance with OSHA 29 CFR 1910.1200 and determined to be hazardous.

EFFECTS OF OVEREXPOSURE: Prolonged repeated skin contact with low viscosity materials may defat the skin resulting in possible irritation and dermatitis. Respiratory irritation, dizziness, nausea, loss of consciousness. Prolonged exposure to high concentrations of gasoline has caused kidney damage and kidney cancer in rats and liver cancer in mice. See MSDS toxicology

section for additional data.

EMERGENCY RESPONSE DATA: Clear Liquid. Extremely flammable. Vapor accumulation could flash and/or explode if in contact with open flame. DOT ERG No. : 128

4. FIRST AID MEASURES

EYE CONTACT: Flush thoroughly with water. If irritation occurs, call a physician.

SKIN CONTACT: Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse.

INHALATION: Remove from further exposure. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance and call a physician. If breathing has stopped, use mouth to mouth resuscitation.

INGESTION: Do not induce vomiting. Give 1 to 2 glasses of water. Get medical assistance.

NOTE TO PHYSICIANS: Material if aspirated into the lungs may cause chemical pneumonitis. Treat appropriately.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Carbon Dioxide, Foam, Dry Chemical, Water Fog.

SPECIAL FIRE FIGHTING PROCEDURES: Evacuate area. Use water to keep fire exposed containers cool. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect personnel attempting to stop leak. Water spray may be used to flush spills away from exposures. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

SPECIAL PROTECTIVE EQUIPMENT: For fires in enclosed areas, fire fighters must use self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Extremely flammable. Vapor accumulation could flash and/or explode if in contact with open flame. Flash Point C(F): -40(-40) (ASTM D-56). Flammable limits - LEL: 1.1%, UEL: 7.6%.

NFPA HAZARD ID: Health: 0, Flammability: 3, Reactivity: 0

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES: Report spills as required to appropriate authorities. U. S. Coast Guard regulations require immediate reporting of spills that could reach any waterway including intermittent dry creeks. Report spill to Coast Guard toll free number (800) 424-8802. In case of accident or road spill notify CHEMTREC (800) 424-9300.

PROCEDURES IF MATERIAL IS RELEASED OR SPILLED: Adsorb on fire retardant treated sawdust, diatomaceous earth, etc. Shovel up and dispose of at an appropriate waste disposal facility in accordance with current applicable laws and regulations, and product characteristics at time of disposal. Eliminate all ignition sources. Runoff may create fire or explosion hazard in sewer system.

ENVIRONMENTAL PRECAUTIONS: Prevent spills from entering storm sewers or drains and contact with soil.

PERSONAL PRECAUTIONS: See Section 8

7. HANDLING AND STORAGE

HANDLING: Avoid contact with skin. Avoid inhalation of vapors or mists. Use in well ventilated area away from all ignition sources. The U. S. Occupational Safety and Health Administration (OSHA), finalized an updated regulation on benzene on September 11, 1987. This standard exempts the storage, transportation, distribution, dispensing, sale or use of gasoline, motor fuels, or other fuels containing benzene, subsequent to the final discharge from bulk wholesale storage facilities. Certain indoor motor fuel dispensing operations are covered regardless of the exemption. The standard establishes requirements covering potential employee exposures, container labeling, medical programs, and employee training. Refer to Chapter 29 of the Code of Federal Regulations (CFR) part 1910.1028 for specific guidance. The OSHA mandated label of "Danger. Contains Benzene. Cancer Hazard. " is required only at affected operations.

STORAGE: Drums must be grounded and bonded and equipped with self-closing valves, pressure vacuum bungs and flame arresters. Store away from all ignition sources in a cool area equipped with an automatic sprinkling system. Outside or detached storage preferred. Storage containers should be grounded and bonded.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION: Use in well ventilated area with local exhaust ventilation. Ventilation required and equipment must be explosion proof. Use away from all ignition sources.

RESPIRATORY PROTECTION: Approved respiratory equipment must be used when airborne concentrations are unknown or exceed the TLV.

EYE PROTECTION: If splash with liquid is possible, chemical type goggles should be worn.

SKIN PROTECTION: If prolonged or repeated skin contact is likely, impervious gloves should be worn. Good personal hygiene practices should always be followed.

Substance Name (CAS-No.)	Source	---TWA---		----STEL---		NOTE
		ppm	mg/m3	ppm	mg/m3	
SUPER UNLEADED GASOLINE	OSHA	300	900	500	1500	
	ACGIH	300	890	500	1480	
BENZENE (71-43-2)	OSHA	1		5		
	ACGIH	0.5	1.6	2.5	8	

NOTE: Limits shown for guidance only. Follow applicable regulations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical physical properties are given below. Consult Product Data Sheet for specific details.

APPEARANCE: Liquid
COLOR: Clear
ODOR: Hydrocarbon
ODOR THRESHOLD-ppm: NE
pH: NA
BOILING POINT C(F): 38(100)
MELTING POINT C(F): NA
FLASH POINT C(F): -40(-40) (ASTM D-56)
FLAMMABILITY: NE
AUTO FLAMMABILITY C(F): NE
EXPLOSIVE PROPERTIES: NA
OXIDIZING PROPERTIES: NA
VAPOR PRESSURE-mmHg 20 C: > 400.0
VAPOR DENSITY: 3.0
EVAPORATION RATE: NE
RELATIVE DENSITY, 15/4 C: 0.7-0.76
SOLUBILITY IN WATER: Negligible
PARTITION COEFFICIENT: NE
VISCOSITY AT 40 C, cSt: < 1.0
VISCOSITY AT 100 C, cSt: NA
POUR POINT C(F): NA
FREEZING POINT C(F): NE
VOLATILE ORGANIC COMPOUND: NE
NA=NOT APPLICABLE NE=NOT ESTABLISHED D=DECOMPOSES

FOR FURTHER TECHNICAL INFORMATION, CONTACT YOUR MARKETING REPRESENTATIVE

10. STABILITY AND REACTIVITY

STABILITY (THERMAL, LIGHT, ETC.): Stable.
CONDITIONS TO AVOID: Heat, sparks, flame and build up of static electricity.
INCOMPATIBILITY (MATERIALS TO AVOID): Halogens, strong acids, alkalies, and oxidizers.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide.
HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL DATA

---ACUTE TOXICOLOGY---

ORAL TOXICITY (RATS): Practically non-toxic (LD50: greater than 2000 mg/kg). ---Based on testing of similar products and/or the components.
DERMAL TOXICITY (RABBITS): Practically non-toxic (LD50: greater than 2000 mg/kg). ---Based on testing of similar products and/or the components.
INHALATION TOXICITY (RATS): Practically non-toxic (LC50: greater than 5 mg/l). ---Based on testing of similar products and/or the components.

EYE IRRITATION (RABBITS): Practically non-irritating.
SKIN IRRITATION (RABBITS): Practically non-irritating. (Primary Irritation Index: greater than 0.5 but less than 3). ---Based on testing of similar products and/or the components.
OTHER ACUTE TOXICITY DATA: Inhalation of vapors/mists may cause respiratory system irritation.

---CHRONIC TOXICOLOGY (SUMMARY)---

Recent studies with laboratory animals have shown that gasoline vapors administered in high concentrations over a prolonged period of time (two year life time studies) caused kidney damage and kidney cancer in male rats and liver cancer in female mice. These effects were not seen in female rats or male mice. Generally, human exposures to gasoline vapors are considerably less than those used in the animal toxicity studies. As far as scientists know, low level or infrequent exposure to gasoline vapors is unlikely to be associated with cancer or other serious diseases in humans. Prolonged repeated skin contact with low viscosity materials may defat the skin resulting in possible irritation and dermatitis.

---OTHER TOXICOLOGY DATA---

Gasoline consists of a complex blend of petroleum/processing derived paraffinic, olefinic, naphthenic and aromatic hydrocarbons which may contain up to 5 percent benzene, with 1-2 percent being typical in the United States; and low levels of multifunctional additives. Repeated exposure to low levels of benzene (<100 ppm) has been reported to result in blood abnormalities in both animals and humans, including anemia and, in rare cases, leukemia. These effects were not observed in laboratory animals following repeated exposure to vapors from unleaded gasoline containing 2 percent benzene.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE AND EFFECTS:

ECOTOXICITY: Not established.

MOBILITY: Not established.

PERSISTENCE AND DEGRADABILITY: Not established.

BIOACCUMULATIVE POTENTIAL: Not established.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Product is suitable for burning for fuel value in compliance with applicable laws and regulations.

RCRA INFORMATION: Disposal of unused product may be subject to RCRA regulations (40 CFR 261). Disposal of the used product may also

be regulated due to ignitability, corrosivity, reactivity, or toxicity as determined by the Toxicity Characteristic Leaching Procedure (TCLP).

BENZENE: 2.0000 PCT (TCLP)
LEAD: .0016 PCT (TCLP)
FLASH: -40(-40) C(F)

14. TRANSPORT INFORMATION

USA DOT:

SHIPPING NAME: Gasoline
HAZARD CLASS & DIV: 3
ID NUMBER: UN1203
ERG NUMBER: 128
PACKING GROUP: PG II
STCC: 4908178
DANGEROUS WHEN WET: No
POISON: No
LABEL(s): Flammable Liquid
PLACARD(s): Flammable
PRODUCT RQ: NA
MARPOL III STATUS: NA

IMO:

HAZARD CLASS & DIV: 3
UN NUMBER: 1203
PACKING GROUP: PG II
SHIPPING NAME: Gasoline
LABEL(s): Flammable Liquid
MARPOL III STATUS: NA

ICAO/IATA:

HAZARD CLASS & DIV: 3
ID/UN Number: 1203
PACKING GROUP: PG II
SHIPPING NAME: Gasoline
SUBSIDIARY RISK: NA
LABEL(s): Flammable Liquid

15. REGULATORY INFORMATION

Governmental Inventory Status: All components comply with TSCA.

EU Labeling:

Symbol: F+ Extremely flammable.

Risk Phrase(s): Not applicable.

Safety Phrase(s): S16/2-24/23-29/43-46.

Keep away from sources of ignition - No Smoking. Keep out of reach of children. Avoid contact with skin. Do not breathe vapors. Do not empty into drains. In case of fire use foam/dry powder/CO2/HALON. If swallowed, seek medical advice immediately and

show this container or label.

Contains: Motor Gasoline.

U.S. Superfund Amendments and Reauthorization Act (SARA) Title III:
This product contains no "EXTREMELY HAZARDOUS SUBSTANCES".

SARA (311/312) REPORTABLE HAZARD CATEGORIES:
FIRE CHRONIC ACUTE

This product contains the following SARA (313) Toxic Release
Chemicals:

CHEMICAL NAME	CAS NUMBER	CONC.
SUPER UNLEADED GASOLINE		100%
BENZENE (COMPONENT ANALYSIS)	71-43-2	2%

The following product ingredients are cited on the lists below:

CHEMICAL NAME	CAS NUMBER	LIST CITATIONS
SUPER UNLEADED GASOLINE (100.00%)		1, 8, 16, 19, 20, 21, 22, 23, 25
BENZENE (COMPONENT ANALYSIS) (2.00%)	71-43-2	1, 2, 4, 6, 9, 10, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26

--- REGULATORY LISTS SEARCHED ---

1=ACGIH ALL	6=IARC 1	11=TSCA 4	16=CA P65 CARC	21=LA RTK
2=ACGIH A1	7=IARC 2A	12=TSCA 5a2	17=CA P65 REPRO	22=MI 293
3=ACGIH A2	8=IARC 2B	13=TSCA 5e	18=CA RTK	23=MN RTK
4=NTP CARC	9=OSHA CARC	14=TSCA 6	19=FL RTK	24=NJ RTK
5=NTP SUS	10=OSHA Z	15=TSCA 12b	20=IL RTK	25=PA RTK
				26=RI RTK

Code key: CARC=Carcinogen; SUS=Suspected Carcinogen; REPRO=Reproductive

16. OTHER INFORMATION

Precautionary Label Text:

GASOLINE

FOR USE AS A MOTOR FUEL ONLY.

DANGER.

EXTREMELY FLAMMABLE.

HARMFUL OR FATAL IF SWALLOWED.
VAPOR HARMFUL.

LONG-TERM EXPOSURE TO VAPORS HAS
CAUSED CANCER IN LABORATORY ANIMALS.

KEEP AWAY FROM HEAT, SPARKS AND FLAME.
AVOID PROLONGED BREATHING OF VAPOR.
KEEP CONTAINER CLOSED.
USE ONLY WITH ADEQUATE VENTILATION.
NOT TO BE USED AS A SKIN CLEANSING AGENT.
NEVER SIPHON BY MOUTH.
KEEP AWAY FROM EYES AND SKIN.
FAILURE TO USE CAUTION MAY CAUSE SERIOUS INJURY OR ILLNESS.

FIRST AID: IF SWALLOWED, DO NOT INDUCE VOMITING.
CALL A PHYSICIAN IMMEDIATELY.

IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING,
GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH AND
CALL A PHYSICIAN.

ATTENTION.

EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE, INCLUDING
FLAMMABLE OR EXPLOSIVE VAPORS, DO NOT CUT, PUNCTURE OR
WELD ON OR NEAR CONTAINER. ALL LABEL WARNINGS AND
PRECAUTIONS MUST BE OBSERVED UNTIL CONTAINER HAS BEEN
THOROUGHLY CLEANED OR DESTROYED.

REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN FOR
FURTHER SAFETY AND HEALTH INFORMATION.

FL-154(5-84)

USE: FUEL

NOTE: PRODUCTS OF GULF OIL LIMITED PARTNERSHIP IS NOT FORMULATED TO CONTAIN
PCBS.

INGREDIENT DESCRIPTION	PERCENT	CAS NUMBER
SUPER UNLEADED GASOLINE	100	

Approval Date: May 2007

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT. Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. Gulf Oil Limited Partnership assumes no responsibility for accuracy of information unless the document is the most current available from an official Gulf Oil Limited Partnership distribution system. Gulf Oil Limited Partnership neither represent nor warrant that the format, content or product formulas contained in this document comply with the laws of any other country except the United States of America.

Prepared by: Gulf Oil Limited Partnership